



HYDROFIRE ΕΠΕ

Buildings - Industry - Marine – Waterworks
 END OF AG. PANTELEIMONOS Str. (ELEONAS)
 GR-12241 EGALEO,
 Tel.: +30 210 3412 749-750 Fax: +30 210 3412 406
www.hydrofire.gr, email: info@hydrofire.gr



April 2008

0163EN

ISO 9001: 2000



Chapter 2 - FIRE DEPARTMENT CONNECTIONS

FIRE PROTECTION PRODUCTS

Straight Two-way Male Outlets

A97




- Used as a standpipe roof outlet connection by the fire service. Provides 250 G.P.M. minimum per outlet. Used with straight or angle hose valves to provide water control

Standard equipment:
 Cast brass body with female NPT inlet and male NPT or male hose thread outlets.
 Straight connection.

a	b
4"	2-1/2"
6"	2-1/2"

	4" x 2-1/2"	6" x 2-1/2"
A	4-57/64"	5-23/32"
B	6-57/64"	8-5/8"



SPECIFY THREAD

Straight Three-way Male Outlets

A97




- Used as a standpipe roof outlet connection by the fire service. Provides 250 G.P.M. minimum per outlet. Used with straight or angle hose valves to provide water control

Standard equipment:
 Cast brass body with female NPT inlet and male NPT or male hose thread outlets.
 Straight connection.

a	b
4"	2-1/2"
6"	2-1/2"

	4" x 2-1/2"	6" x 2-1/2"
A	6-21/32"	6-57/64"
B	10-11/16"	10-11/16"
C	5-3/64"	7-3/32"



SPECIFY THREAD